







PRODUCT DESCRIPTION

Introducing the Track Lighted Mirror – a remarkable blend of Italian design and cutting-edge technology that reimagines your daily beauty rituals. The Track's exclusive GHOST Lighting technology conceals the light source when switched off, maximizing the reflective space on the mirror. An interior frame of direct light offers substantial illumination, ideal for makeup application and other beauty-related tasks requiring precision and clarity. Say farewell to foggy mirrors with our defogger and enjoy a pristine reflection, even in steamy bathroom conditions. With CCT selectability, you can toggle between different light temperatures, ensuring the perfect ambiance for your grooming needs. Dial in the ideal brightness level with dimmability. Operate the Track Lighted Mirror easily using the hands-free infrared (IR) sensor that allows you to adjust settings and turn the mirror on or off without ever touching a button. The Track Lighted Mirror isn't just a mirror; it's a testament to Italian design, innovation, and style. Elevate your self-care routine, revel in the spacious reflection, and redefine your space with Track..

FEATURES

- 360 degree direct and ambient wall lighting
- Infrared (No-touch) On/Off switch
- CRI 85+ CCT: Tunable (3000K or 4000K or 6000K) LED rated life: 50000 hours.
- Dimmable.
- 5MM (13/64") Thick glass with safety film backing
- Integraded deffoger
- Easy Installation
- Designed in Italy

SAFETY RATINGS & WARRANTY

- IP44 ETL DAMP listed, Conforms to UL STD 962, Certified CAN/CSA
- 7 Year Warranty
 - See installations instructions for proper installation requirements

GHOST TECHNOLOGY

• GHOST Lighting technology conceals the light source when switched off, maximizing the reflective space on the mirror.







BASE MODELS*

Item #	Finish	Dimensions	Lighting Specifications	Control type	Power Requirement
3-0501-15	N/A	18" (w) x 24"(h) x 1.19" Ext.	CCT 3000-6000K LED 85+ CRI- 4032 initial lumens	Infrared (No-Touch) On/Off Switch	120V, 59W
3-0502-15**	N/A	24"(w) x 36"(h) x 1.19" Ext.	CCT 3000-6000K LED 85+ CRI-6300 initial lumens	Infrared (No-Touch) On/Off Switch	120V, 102.4W
3-0503-15 * *	N/A	36 (w) x 24"(h) x 1.19" Ext.	CCT 3000-6000K LED 85+ CRI-6300 initial lumens	Infrared (No-Touch) On/Off Switch	120V, 102.4W
3-0504-15	N/A	36 (w) x 36"(h) x 1.19" Ext.	CCT 3000-6000K LED 85+ CRI 7812 initial lumens	Infrared (No-Touch) On/Off Switch	120V, 118.6W
3-0505-15	N/A	48 (w) x 36"(h) x 1.19" Ext.	CCT 3000-6000K LED 85+ CRI- 9324 initial lumens	Infrared (No-Touch) On/Off Switch	120V, 149.6W
3-0506-15	N/A	48 (w) x 48"(h) x 1.19" Ext.	CCT 3000-6000K LED 85+ CRI 9324 initial lumens	Infrared (No-Touch) On/Off Switch	120V, 197.6W
3-0507-15	N/A	60 (w) x 42"(h) x 1.19" Ext.	CCT 3000-6000K LED 85+ CRI- 11088 initial lumens	Infrared (No-Touch) On/Off Switch	120V, 205W

^{*} Custom Capabilities
Please enquire about your
specific needs

* * Please note, On 3-0502 and 3-0503 the IR Sensor is located on the bottom right hand side. Due to the sensor location this mirror does not allow 90 degree rotation.

Intertek

