

PIVOT Sconce
3-406-xxxx

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____


DATE _____



-640 White/Aged Brass




-40 Aged Brass



-1540 Black/Aged Brass

LIGHT SOURCE	(1x) 16W LED Array, 3000K, CRI 90
LUMINAIRE POWER	13.82W
RATED LIFE	50000 hr RL
OPTIONAL COLOR TEMPERATURES	3000/3500/4000K LED CCT
LUMEN OUTPUT	Contact oxygen for Lumen Information
INPUT VOLTAGE	120-277V
DRIVER OUTPUT	17W
DIMMING	Triac dimming 10-100%
CONSTRUCTION	Cold Rolled Steel
DIFFUSER	Matte White Acrylic Diffuser.
FINISHES	40 Aged Brass, 640 White/Aged Brass, 1540 Black/Aged Brass
MOUNTING	Installs to a 4" octagonal junction box
STANDARDS	cUL Damp Listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

W:	23"
H:	5.75"
B (Backplate):	4.75"
Ext:	6.5"
M.C:	2.8" From top of fixture

Order example for standard fixture:
3-406-640 (x-xxx: LED Sequence # / -xx: Finish)
 Order example for optional color temperatures: **3-6018-**
27: 2700K, **35:** 3500K, **40:** 4000K

