

OLIO Wall Sconce
3-539-xx

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____




-22 Oiled Bronze



-24 Satin Nickel

LIGHT SOURCE	2 x 10.1W LED, 3000K, CRI 90
LUMINAIRE POWER	24.0W at 120V
RATED LIFE	60000 hr RL
OPTIONAL COLOR TEMPERATURES	2700K, 3500K, 4000K
LUMEN OUTPUT	Delivered: 632 lm (LM-79)
INPUT VOLTAGE	120V to 277V AC, 50/60 Hz
DRIVER OUTPUT	700mA, 29.4W max power
DIMMING	TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 1% current output
CONSTRUCTION	Plated Steel and Glass
DIFFUSER	- White Opal Glass
FINISHES	Oiled Bronze (-22), Satin Nickel (-24)
MOUNTING	4" Octagonal J-Box*, 4" Square J-Box* *Deep J-Box (Required to house driver)
STANDARDS	UL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

W:	7.00"
H:	11.00"
Ext:	4.00"
M.C:	8.25" From top of fixture

Order example for standard fixture:
3-539-24 (x- Voltage - xxx-Sequence # - xx-Finish)
 3: 120V to 277V

Order example for optional color temperatures: **3-539-2724**
 27: 2700K, 35: 3500K, 40: 4000K

