

**PIVOT Sconce**  
**3-406-XXX**

oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_


PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



-640 White/Aged Brass

<b>LIGHT SOURCE</b>	(1x) 16W LED Array, 3000K, CRI 90
<b>LUMINAIRE POWER</b>	13.82
<b>RATED LIFE</b>	50000 hr RL
<b>OPTIONAL COLOR TEMPERATURES</b>	3000/3500/4000K LED CCT
<b>LUMEN OUTPUT</b>	Contact oxygen for Lumen Information
<b>INPUT VOLTAGE</b>	120-277V
<b>DRIVER OUTPUT</b>	TBD
<b>DIMMING</b>	Triac dimming 10-100%
<b>CONSTRUCTION</b>	Cold Rolled Steel
<b>DIFFUSER</b>	Matte White Acrylic Diffuser.
<b>FINISHES</b>	40 Aged Brass, 640 White/Aged Brass, 1540 Black/Aged Brass
<b>MOUNTING</b>	Installs to a 4" octagonal junction box
<b>STANDARDS</b>	cUL Damp Listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



**DIMENSIONS**

<b>W:</b>	<b>23"</b>
<b>H:</b>	<b>5.75"</b>
<b>Ext:</b>	<b>6.5"</b>
<b>M.C:</b>	<b>X" From top of fixture</b>

Note:

Order example for standard fixture:

**3-406-640** (x-xxx: LED Sequence # / -xx: Finish)

